




# Tauris Transit Fully Automatic Strapping Machine



SPECIFICATIONS	
Code	BTP-601B
Description	Tauris Transit Fully Automatic Strapping Machine
Features and Benefits	Reliable and robust strapping head Auto strap feeding Electronic tension control Auto strap ejector Belt transmission Hinged top plates Conveyor speed: 30 metres/minute Multiple strap function for single, double, continuous strapping, or transit mode Up and down stream interlock with complete plug connection Easy bundle flow direction change Strap end ejector
Industries	Print / Corrugated / Food / General
Options	Available on request

SPECIFICATIONS	
Strap Width (mm)	8 / 9 / 12
Tension Range (kg)	7 - 70 *(requires safety devices to meet CE regulations)
Standard Arch Size (mm)	850 (W) x 600 (H) *other arch sizing available on request
Capacity	Up to 18 packages / minute (60Hz) (Cycle speed up to 29 cycles/minute)
Table Height (mm)	825
Weight (kg)	325

The figures above are based off average results from multiple tests, results may vary + or - 10%

National Packaging Machinery products are registered and under trademark of PGL and sold exclusively through selected distributors.

For further information on National Packaging Machinery please email sales@pgl.co.nz, phone 0800 766 662 or contact your distributor.

APRIL 2025

**100% New Zealand Owned & Operated**

