



Mercury High Speed Automatic Strapping Machine



SPECIFICATIONS	
Code	BTP-702-59
Description	Mercury High Speed Automatic Strapping Machine
Features and Benefits	Robust & compact mechanical strapping head High speed up to 65 straps per minute Free access to strap guides (patents registered) Waist-high auto strap feeding Waist-high quick coil change (patents registered) Turnable operating control panel Auto strap ejector Dispenser release switch Sensor controlled heater Low voltage Strap end ejector Front foot bar switch Adjustable table height between 820mm & 920mm
Industries	Print / Corrugated / General
Options	Available on request

SPECIFICATIONS	
Strap Width (mm)	5 / 6 / 9
Tension Range (kg)	1 - 32 *higher tension is on request
Standard Arch Size (mm)	550 (W) x 400 (H) *other arch sizing available on request
Capacity	Up to 65 cycles / minute
Table Height (mm)	820 - 920
Weight (kg)	158

The figures above are based off average results from multiple tests, results may vary + or - 10%

National Packaging Machinery products are registered and under trademark of PGL and sold exclusively through selected distributors.

For further information on National Packaging Machinery please email sales@pgl.co.nz, phone 0800 766 662 or contact your distributor.

APRIL 2025

100% New Zealand Owned & Operated

