




Mercury Transit Fully Automatic Strapping Machine with Press



SPECIFICATIONS	
Code	BTP-702BP
Description	Mercury Transit Fully Automatic Strapping Machine with Press
Features and Benefits	<p>Robust & compact mechanical strapping head with pneumatic press</p> <p>Waist-high auto strap feeding</p> <p>Free access to strap guides (patents registered)</p> <p>Electronic tension control</p> <p>Auto strap ejector</p> <p>Hinged top plates</p> <p>Multiple strap function for single, double, continuous strapping, or transit mode</p> <p>Variable conveyor speed between 10 & 60 m/minute</p> <p>Up and down stream interlock with complete plug connection</p> <p>Easy bundle flow direction change</p> <p>Good to strap small package with min. size 120mm in width and 10mm in height</p> <p>Adjustable table height between 800mm & 900mm</p>
Industries	Corrugated / Food / General
Options	Available on request

SPECIFICATIONS	
Strap Width (mm)	5 / 6 / 9 / 12
Tension Range (kg)	1 - 32 (for 5 / 6 / 9mm) / 1 - 45 (for 12mm) *higher tension is on request
Standard Arch Size (mm)	650 (W) x 500 (H) *other arch sizing available on request
Capacity	Up to 36 packages / minute (Cycle speed up to 65 cycles / minute)
Pneumatic Source	6 bar
Air Consumption	7.5 litre / cycle
Table Height (mm)	800 - 900
Weight (kg)	250



The figures above are based off average results from multiple tests, results may vary + or - 10%

National Packaging Machinery products are registered and under trademark of PGL and sold exclusively through selected distributors.

For further information on National Packaging Machinery please email sales@pgl.co.nz, phone 0800 766 662 or contact your distributor.

APRIL 2025

100% New Zealand Owned & Operated

