



High Speed Fully Automatic Corrugated Strapper



SPECIFICATIONS	
Code	BTP-702C
Description	High Speed Fully Automatic Corrugated Strapper
Features and Benefits	Compact & robust strapping head Siemens PLC Free access to strap guides (patents registered) Hinged roller table Auto strap ejector Patented jammed-strap ejection device Full-width pneumatic press Multiple strap function Variable conveyor speed Strap end ejector Adjustable table height between 700mm & 1000mm
Industries	Corrugated / General
Options	Available on request

SPECIFICATIONS	
Strap Width (mm)	5 / 6 / 9
Tension Range (kg)	1 - 32
Capacity	Up to 33 bundles / minute (single strap) Up to 20 bundles / minute (double straps) (Model: TP-702C-L)
Arch Size (mm)	TP-702C-L 1650 (W) x 450 (H) TP-702C-M 1250 (W) x 450 (H)
Minimum Bundle Size (mm)	200 (W) x 20 (H) x 300 (L)
Bundle Weight (kg)	max 40
Conveyor Speed	15 – 60 m / minute
Table Height (mm)	700 - 1000



The figures above are based off average results from multiple tests, results may vary + or - 10%

National Packaging Machinery products are registered and under trademark of PGL and sold exclusively through selected distributors.

For further information on National Packaging Machinery please email sales@pgl.co.nz, phone 0800 766 662 or contact your distributor.

APRIL 2025

100% New Zealand Owned & Operated

