



Fully Automatic Longitudinal Strapping Machine



SPECIFICATIONS	
Code	BTP-702NL
Description	Fully Automatic Longitudinal Strapping Machine
Features and Benefits	Robust & compact mechanical strapping head Auto self-adjusting strap chute (patents registered) Automatic tension control for various bundle dimensions (patents registered) Up and down stream interlock with complete plug connection Fully automatic operation with variable conveyor speed Siemens PLC and touch panel Free access to strap guides (patents registered) Easy access to strapping head (patents registered) Strap end ejector Adjustable table height between 800mm & 900mm Auto strap ejector
Industries	Print
Options	Available on request

SPECIFICATIONS	
Strap Width (mm)	5 / 6 / 9
Tension Range (kg)	1 - 32
Capacity	Up to 31 bundles / minute
Bundle Size (mm)	Width max 450 / min 120 Length max 500 / min 210 Height max 400 / min 10
Bundle Weight (kg)	max 25
Pneumatic Source	6 bar
Air Consumption	8.53 litre / cycle
Table Height (mm)	800 - 900
Weight (kg)	475



The figures above are based off average results from multiple tests, results may vary + or - 10%

National Packaging Machinery products are registered and under trademark of PGL and sold exclusively through selected distributors.

For further information on National Packaging Machinery please email sales@pgl.co.nz, phone 0800 766 662 or contact your distributor.

APRIL 2025

100% New Zealand Owned & Operated

