



# Fully Automatic Strapping Machine



SPECIFICATIONS	
Code	BTP-702NS
Description	Fully Automatic Strapping Machine
Features and Benefits	<p>Robust &amp; compact mechanical strapping head</p> <p>Automatic tension control for various bundle dimensions (patents registered)</p> <p>Dual pneumatic press</p> <p>Up and down stream interlock with complete plug connection</p> <p>Fully automatic operation with variable conveyor speed</p> <p>Siemens PLC and touch panel</p> <p>Free access to strap guides (patents registered)</p> <p>Easy access to strapping head (patents registered)</p> <p>Strap end ejector</p> <p>Adjustable table height between 800mm &amp; 900mm</p> <p>Auto strap ejector</p>
Industries	Print
Options	Available on request

SPECIFICATIONS	
Strap Width (mm)	5 / 6 / 9
Tension Range (kg)	1 - 32
Capacity	<p>Up to 42 bundles/minute (single strap)</p> <p>Up to 24 bundles/minute (double straps)</p>
Bundle Size (mm)	<p>Width    max 500 / min 120</p> <p>Height   max 390 / min 10</p>
Bundle Weight (kg)	max 25
Pneumatic Source	6 bar
Air Consumption	2.65 litre / cycle
Table Height (mm)	800 - 900
Weight (kg)	430



The figures above are based off average results from multiple tests, results may vary + or - 10%

National Packaging Machinery products are registered and under trademark of PGL and sold exclusively through selected distributors.

For further information on National Packaging Machinery please email [sales@pgl.co.nz](mailto:sales@pgl.co.nz), phone 0800 766 662 or contact your distributor.

APRIL 2025

**100% New Zealand Owned & Operated**

