



Mercury Wash Down Automatic Side Seal Strapping Machine



SPECIFICATIONS	
Code	BTP-702YM
Description	Mercury Wash Down Automatic Side Seal Strapping Machine
Features and Benefits	Robust and compact strapping head High strapping speed up to 35 packages / minute Water proof design with internal heating device Control panel with LCD display Free access to strap guides (patents registered) Downward tension force IP54 rated protection of electric control unit Up and down stream interlock Inner strap dispenser design Adjustable table height from 445mm to 645mm
Industries	Aquaculture / Horticulture / Food / General
Options	Available on request

SPECIFICATIONS	
Strap Width (mm)	5 / 6 / 9 / 12
Tension Range (kg)	1 - 32 (for 5 / 6 / 9mm) / 1 - 45 (for 12mm) *higher tension is on request
Standard Arch Size (mm)	600 (W) x 650 (H)
Capacity	Up to 60 cycles / minute
Table Height (mm)	445 - 645
Weight (kg)	281

The figures above are based off average results from multiple tests, results may vary + or - 10%

National Packaging Machinery products are registered and under trademark of PGL and sold exclusively through selected distributors.

For further information on National Packaging Machinery please email sales@pgl.co.nz, phone 0800 766 662 or contact your distributor.

APRIL 2025

100% New Zealand Owned & Operated

