



Castor III Fully Automatic Horizontal Pallet Strapping Machine



SPECIFICATIONS	
Code	BTP-733H
Description	Castor III Fully Automatic Horizontal Pallet Strapping Machine
Features and Benefits	ARES BTP-733-SH strapping head Index strapping head Strap guide arm Safety rack Friction weld sealing technology Siemens PLC and HMI Free access to strap guides Swivel dispenser set Adjustable sealing and cooling time Strap end ejector Preprogram setting Easy to replace strapping head
Industries	Horticulture / General
Options	Available on request

SPECIFICATIONS	
Strap Type	PP / PET strapping
Strap Width (mm)	12 / 15.5 / 19
Tension Range (N)	1100 - 3200 (standard) 200 - 1200 (option)
Capacity	Up to 60 pallets / hour (3 parallel straps)
Minimum Strapping Height (mm)	(a) With conveyor: 160 above conveyor surface (b) Without conveyor: 240 above floor
Maximum Package Height (mm)	2,200 (standard) 2,700 (option)
Strap Core Size (mm)	406 / 200 / 230 / 280
Pneumatic Source	6 bar
Air Consumption	7.1 litre / cycle



The figures above are based off average results from multiple tests, results may vary + or - 10%

National Packaging Machinery products are registered and under trademark of PGL and sold exclusively through selected distributors.

For further information on National Packaging Machinery please email sales@pgl.co.nz, phone 0800 766 662 or contact your distributor.

APRIL 2025

100% New Zealand Owned & Operated

